

Applications


- Click-on type one hole straps for rigid conduit or EMT.
- Provides support for the conduits, as required by the National Electrical Code.

Material/Finish

- Steel/zinc plated



Illustrated Dimensions



1/2	47.0 (1.85)	20.3 (0.80)	15.7 (0.62)	6.4 (0.25)	GR1-050
3/4	31.0 (1.22)	23.4 (0.92)	19.1 (0.75)	6.4 (0.25)	GR1-075
1	67.3 (2.65)	29.2 (1.15)	22.1 (0.87)	7.9 (0.31)	GR1-100
1-1/4	75.7 (2.98)	35.8 (1.41)	25.1 (0.99)	9.7 (0.38)	GR1-125
1-1/2	89.2 (3.51)	40.9 (1.61)	25.4 (1.00)	11.2 (0.44)	GR1-150
2	105.9 (4.17)	50.0 (1.97)	29.0 (1.14)	13.5 (0.53)	GR1-200
2 - 1/2	126.7 (4.99)	72.4 (2.85)	31.5 (1.24)	13.5 (0.53)	GR1-250
3	141.0 (5.55)	88.1 (3.47)	31.8 (1.25)	13.5 (0.53)	GR1-300

Trade Size (Inches)	Dimensions in Millimeters (Inches)				Model
	A	B	C	D	

Applications


- Snap-on type two hole straps for rigid conduit and IMC are used where higher load bearing supports are desired.

Material/Finish

- Steel/zinc plated



Illustrated Dimensions



1/2	62.7 (2.47)	21.8 (0.86)	15.7 (0.62)	4.8 (0.19)	GR2-050
3/4	71.6 (2.82)	27.9 (1.10)	17.3 (0.68)	4.8 (0.19)	GR2-075
1	85.9 (3.38)	32.3 (1.27)	19.1 (0.75)	6.4 (0.25)	GR2-100
1-1/4	101.6 (4.00)	42.7 (1.68)	21.8 (0.86)	6.4 (0.25)	GR2-125
1-1/2	107.7 (4.24)	42.4 (1.67)	22.1 (0.87)	6.4 (0.25)	GR2-150
2	112.8 (4.44)	50.3 (1.98)	23.9 (0.94)	9.7 (0.38)	GR2-200
2 - 1/2	131.8 (5.19)	72.9 (2.87)	24.9 (0.98)	9.7 (0.38)	GR2-250

Trade Size (Inches)	Dimensions in Millimeters (Inches)				Model
	A	B	C	D	